



(GB) USER'S INFORMATION FOR FACE SHIELD

TYPE RW 101 RW 102

CAUTION

This face shield does not provide unlimited face protection. For your con protection read these instructions completely before using this face-protection. REQUIREMENTS

This face shield complies with the requirements of the European Directive 89/686/CEE annex if by means of the European Standard EN1662001 or EN1731:2006 "Personal Eye Protection-Specification. STORAGE

n use, it is recommended to store the face shield in a clean and dry polybag or case for visor protection.

When the time, it is not interested to be a fact and only proposed to see for the whole duration of exposure to husards, leave the week, area of durations or intusion occurs, or if the face shield becomes duration of exposure to husards, leave the week, area of durations or intusion occurs, or if the face shield becomes duratinged.

CLEANING AND MAINTENANCE

clean and rinse in warm soapy water and dry with a soft cloth. th are in contact with the wearer shall be disinfected by alcoho

To maintain your face theid in good condition:


1, Do not use thrivince materials clean and rines in warm soapy water and dry with wolf cloth,

2. Any part of face protector which are in contact with the wearer shall be distinfected by alcohe

FEELD OF USE.

This fine theided is designed to protect as user against eye and face injuries through information

shield is marked on the brow protection and visor with a series of numbers and symbol use indi
the protection capabilities and performance characteristics of the face-protector. As oppni
similarly as follows:



Les Unraheagh.

Symbol of prosection against increased robutness as a speed 5.1m/s,
Symbol of prosection against high-speed particle, love energy (45m/s).
Symbol of prosection against high-speed particle, mentium energy (120m/s).
Symbol of Prosection against objects and speakes of [hould.]
Number of the standard, which the groduct fulfills
Number of the standard, which the groduct fulfills
Identification of the manifecture.

REPLACEMENT OF SPARE PARTS, ACCESSORIES AND PURCTIONS FOR FITTING Only use original spare parts. To rep DURATION OF USE

respect for damage regularly. When the face-protector has become brittle face shield should be replaced. WARNING:

WARNING:

This product is for face protection against moderate impact hazardighat NOT inthreakable.

Do not modify or alier the face protection,
Figled or seminded screen reduce vision and terriously reduce protection and should be immediately replaced.

This face protector has not any filtering action. It does not protect against mohen metal against, hot social or electrical has Always check with supervision personnel as ensure you are being giffen the proper protection guide as working conditionable European associates.

The materials which may come into contact with the wearer's skin could of if the symbols F, B and A are not common to both ocaler and the frame to

CERTIFICATION

CE mad, was its sed by the notified body 0.194 INSPEC International Ltd -56 Leslie Hough Way Salfort Greater Manchester M6 6AU



GB Installations Instructions for RW 302A/O

(Read all instructions and warnings before wearing)

RW 302A and RW 3020 are sometimes shipped with the suspension disengaged from the shell to prevent distortion during shipping. The suspension must be correctly installed according to the instructions to assure proper fit and protection.

RW 302A and RW 3020 meet EN 397 Standard.

1. Turn hard hat upside down. Place suspension inside hard hat with brow pad toward front bill, See Rigures 1 and 3.

Rending the hanger key outward at hinge, insert key into respective key slot (Figure 2). Push key firmly until i snaps into place. Repeat for each hanger key.

Adjusting the Suspension Size: - Standard Suspension

Squeeze top and bottom edges of rear buckle together with your thumb and forefinger (Figure 4).

At the same time, decrease headband see by fliding right hand portion of headband through buckle.

Place the hard hat on your head and pull is down allowing headband to expand until it feels comfartable. Dr. NOT OVER TIGHTEN.

Ratchet Suspension

1. Turn ratchet knob count clockwise until headband opens to largest size.

Place hard hat on your head, Tuff ratchet knob clockwise until headband is cornfortable (Figure 5). DO NOT OVER TIGHTEN.

WARNINGS

Hard hats are designed to provide limited protection to the head by reducing the force of falling objects striking the top of the hard hat shell. While limited protection is provided in other parts of the shell, this hard hat was not designed to provide front, side or rear impact protection. Avoid contact with electrical wires. Inspect your hard hat shell and suspension regularly. Check immediately if you notice any signs of wear, damage, abuse or environmental degradation. If the hard hat has sustained a forcible blow (impact), dispose of it immediately, even if damage is not visible.

Clean the hard hat and suspension with mild soap and lukewarm water. Do not use paints solveats, chemicals, adhesives, gasoline or like substances on this hat. The impact resistance and other protective properties of the hat may be destroyed by such substances. These dangerous conditions may not be apparent or readily detectable by the user.





INSTRUCTIONS FOR USE OF EAR MUFF TYPE: RW 666

APPLICATION:

When worn properly and given adequate care, it provides excellent projection that filters high frequency noise. We find most noise problem are from dynamic machines such as workshop equipment and motor saws.

REQUIREMENTS

This hearing protector bomplies with the requirements of the European Directive 89/686.EEC annex II by means of the European Standards EN152 3:2002 "Hearing protectors-Safety requirements and testing Part 3: Ear muffs attached safety helmet".

MARKING:

The appropriate marking* can be found on the cups.

*CB mark was issued by the notified body 0403.

Finnish Institute of Occupational Health Topelluksenkatu 41 a A, FI-00250 Helsinki Finland

- 1. Insert connector of the ear mult into cap alots.
 2. Place cap on head with multi-til outer "rest" position. Be sure cap is placed properly on head.
 1. Lower mult against high and coust ear cups to adequate height and pressure so they seal firmly against head.
- 4 Make sure cap suspension does not interfere with seal.

 Put the ear muffs of before exposing yourself to noise and wear them during the whole noise

WARNING:

- This ear muff is of 'normal size range' complying with EN352-3; it will fit the majority of
- 2. If data given in that leaflet are taken into account, salety can be greatly undermined.

Frequency(Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	14:0	13,8	19.4.	27.6	34.4	33.1	30.1	26.7
Standard Deviation (dB)	3.2	3,8	2.5	2.1	3.7	2.7	2.8	5.0
Assumed protection (dB)	10.8	10.0	16.9	25.5	30.7	30.4	27.3	21.8
	NR-26	41:27	M/26	L:18				-

WEIGHT OF THE EAR-MUFF:210g

CLEANING:

Cleaning with warm soapy water, do not use of linic solvents or alcohol for cleaning.

DISINFECTION:

I. It is required to disinfect the ear-muff every 3 months according to the uso.

2. Any part of the ear muff which is in contact with the wearer shall be disinfected. appropriate solution.

STORAGE:

When not in use, it is recommended to store the ear muff in a clear dry polybag.

